

Fume Hoods

Catalog No. F50020-1010 and F50020-2010

F50020-1010



F50020-2010



Principles of Operation

These SP Bel-Art Fume Hoods feature an all-clear polycarbonate body and sash. The polycarbonate sash can be fixed in place at three locations. Use the two black knobs (A) to raise and lower the sash to the desired height. The sidetracks have three holes that are provided for the detent pins (B) which hold the door in position at the selected level.

When the detent pins are in the lowest position, a 1/4" wide gap will be left beneath the door. This gap will allow air to enter and sweep the deck. The detent pins should not be removed completely but should always be in one set of holes. An exhaust system capable of drawing 200 cfm (free air) is recommended for use with these fume hoods.

Do not place very hot items directly in contact with the plastic material. A practical temperature limit is 80°C (176°F). Do not use abrasive cleaners on the clear door as it will scratch and become cloudy.

If you require further assistance in the installation, operation, or use of this SP Bel-Art product, please contact our Technical Services Department at 1-973-694-0500, x4269.

CATALOG NO.	F50020-1010	F50020-2010
Overall External Dims: (W x D x H)	25 $\frac{1}{8}$ x 24 x 26 $\frac{1}{8}$ " (65.7 x 61 x 66.4cm)	43 $\frac{3}{8}$ x 24 x 26 $\frac{1}{8}$ " (111.4 x 61 x 66.4cm)
Construction Materials:	Clear Polycarbonate Body and Sash	
Exhaust Port Quantity	1	1
Exhaust Port O.D.	6" (152mm)	
Exhaust Port I.D.	5.5" (140mm)	

Your opinion counts! Write a product review at www.sp-belart.com



Bel-Art Products, a part of SP

661 Route 23 South, Wayne, NJ 07470 USA

Tel: 973-694-0500 | cservice.belart@spindustries.com

sp-belart.com

Individual use varies. Bel-Art Products/SP assumes no obligation or liability for any advice furnished by it or for results obtained with respect to these products. All advice is given and accepted at the user's risk. For warranty information visit belart.com/corporate. For warranty information and to register your product visit sp-belart.com/corporate

