

INSTRUCTIONS



Frigimat® Jr. Dry Ice Maker

Catalog Number 38886-0000

The Frigimat® Jr. is a complete mechanical appliance designed to fit any standard liquid carbon dioxide cylinder. It consists of a brass fitting which screws onto the liquid CO₂ cylinder thread, a plastic cone and collection bag with clamp. A liquid CO₂ cylinder with an internal siphon tube is required.

To assemble, slide the open end of the bag over the plastic cone and tie the tabs. Next, slide the plastic ring over the brass fitting, cone and bag until it tightens. Finally, follow the ring with the screw clamp and tighten the clamp next to the ring. Open the liquid CO₂ cylinder valve about $\frac{3}{4}$ of a turn. The collection bag will begin to fill immediately with dry ice flakes. When the bag is full, close the



valve tightly and tap the cone gently to remove any ice sticking to it. The ice may be squeezed into a hard pack or left in flake form depending upon its intended use.

CAUTION: Wear gloves when handling dry ice.

Replacement Parts:
F38886-0001 Extra Bags

BEL-ART PRODUCTS

661 Route 23 South, Wayne, NJ 07470-6814 USA
TEL: 1-800-4BEL-ART • FAX: 973-694-7199 • www.belart.com

999320712

03/02

Scienceware®, Frigimat® are reg. TM of Bel-Art Products
Bel-Art Products assumes no obligation or liability for any advice furnished by it, or for results obtained with respect to these products. All such advice is given and accepted at the buyer's risk.

OTHER FINE SCIENCEWARE® PRODUCTS FOR YOUR LABORATORY

Frigimat® Dry Ice Maker



The Frigimat® Dry Ice Maker eliminates the need to buy large quantities of dry ice, producing a solid 16 ounce (454gm) block in one to two minutes. Removing the dry ice block requires just 30 seconds, and the Frigimat® Dry Ice Maker is then ready to make another block of dry ice. Each cylinder of liquid CO₂ will make 8 or 9 blocks of dry ice. Made of epoxy-coated steel with an aluminum ice chamber and brass valves. Rubber feet give cushioned support. Dimensions are 12"x6 $\frac{1}{2}$ "x5 high (30x17x13cm). Shipping weight 12lbs (5.5kg). Includes a six foot (1.8m) nickel-plated copper connecting tube with standard GCA 320 thread couplings for easy attachment to a LCO₂ cylinder. Threaded inlets can be supplied for LCO₂ cylinder fittings in Europe or Japan.

H38878-0010 with USA LCO₂ cylinder fitting
H38878-0012 with European LCO₂ cylinder fitting
H38878-0013 with Japanese LCO₂ cylinder fitting

CAUTION: Wear gloves when handling dry ice.



BEL-ART PRODUCTS

661 Route 23 South, Wayne, NJ 07470-6814 USA
TEL: 1-800-4BEL-ART • FAX: 973-694-7199 • www.belart.com